

Two Piece Toilet
Vitreous China



FEATURES

• **4191 Atlas®**

Bowl: 4290 Atlas® (1.6 gpf / 6.0 lpf) regular rim, vitreous china, low consumption, floor-mounted, siphon wash, close-coupled combination with bolt caps.

Tank: 4471 Atlas® 12" roughing-in vitreous china tank and cover with anti-siphon ballcock and flushvalve.

• **4194 Atlas® Plus**

Bowl: 4290 Atlas® (1.6 gpf / 6.0 lpf) regular rim, vitreous china, low consumption, floor-mounted, siphon wash, close-coupled combination with bolt caps.

Tank: 4474 Atlas® Plus 12" roughing-in insulated vitreous china tank and cover with anti-siphon ballcock and flushvalve.

• **4196 Atlas®**

Bowl: 4295 Atlas® (1.6 gpf / 6.0 lpf) elongated rim, vitreous china, low consumption, floor-mounted, siphon wash, close-coupled combination with bolt caps.

Tank: 4471 Atlas® 12" roughing-in vitreous china tank and cover with anti-siphon ballcock and flushvalve.

• **4199 Atlas® Plus**

Bowl: 4295 Atlas® (1.6 gpf / 6.0 lpf) elongated rim, vitreous china, low consumption, floor-mounted, siphon wash, close-coupled combination with bolt caps.

Tank: 4474 Atlas® Plus 12" roughing-in insulated vitreous china tank and cover with anti-siphon ballcock and flushvalve.

NOTES

- Fixtures conform with dimension and performance requirements of ASME A112.19.2M.
- Toilet seat not included.

WATER ECONOMY FACTS

Average Gallons Per Flush	20 PSI	50 PSI	80 PSI
4191, 4194 Regular Rim	1.52	1.55	1.57
4196, 4199 Elongated Rim	1.54	1.56	1.60
Trapway.....	2"		
Water Surface.....	9 1/2" x 8"		
Water Seal.....	2 5/8"		



