



36" One Piece Shower Cast Acrylic

FEATURES

- **A 3634.01 - Olympia Shower Module**
 - 36" x 34" x 84" (nominal)
 - Clear acrylic towel bar
 - Two accessory shelves
- **A 3634.01 R/L - Olympia Shower Module With Steam**
 - 36" x 34" x 84" (nominal)
 - A 3634.01 as listed above plus:
 - Digital timer
 - Steam generator, 240 VAC, 20 Amp for installation within 15 feet of shower
 - Chrome steam outlet
 - Fold-up seat, specify right or left side
 - Factory installed anodized aluminum door channels
 - Tempered clear glass hinged door and side panels for field installation

The unit is thermoformed from a solid color lucite XL® high gloss acrylic sheet into a one piece, totally seamless unit. This unit is reinforced on the back with a composite matrix which has a backside fire rating of "B" and a flame spread of 75. The shower models are pre-drilled to accept a 2" shower drain (supplied by others).

NOTES

- **Dimensions:** 36" x 33 1/2" x 83 1/2" with flange
- **Shipping Weight:** A 3634.01 - 160 lbs.
A 3634.01S - 280 lbs.
- **Certifications:** ANSI Z124.2
- Illustrated installation instructions included.

OPTIONS

- Canopy light (factory drilled for field installation) 60 watt dome mounted shower light. White lens only. (APT1)
- 2" plastic drain with chrome plated strainer. (PD2)
- 2" cast brass drain with chrome plated strainer. (H30)
- Recommended enclosures include Showerite Door models 830HR.
- Lucite® acrylic sheet containing Microban® antibacterial protection. Available in white and bone only. (MBP)

Steam Unit Only:

- Polished brass trim.

