

Molded-Stone® Serv-A-Sink® Twin Compartment Laundry Tubs



FEATURES

- **LTD II Wall Hung Serv-A-Sink®**

Model LTD II Twin Tub is furnished with and supported by two mounting brackets of heavy gauge galvanized steel capable of being secured to the wall with mechanical fasteners. Model LTD II side fillers which are assembled in the field to the mounting brackets are made of white molded plastic polymer. LTD II is supplied with 4" or 8" knockout center set faucet holes which are field drilled.

- **FLTD II Floor Mounted Serv-A-Sink®**

Model FLTD II Twin Tub is furnished with and supported by white baked enamel steel angle legs that slip into molded retainers and/or sockets for rigid friction fit. Legs are supplied with leveling devices.

NOTES

- Model LTD II Twin Tub has an overall outside dimensions of 40" x 24" x 13 ⁷/₈", and inside dimensions (each compartment) of 19" x 18 ⁷/₈" x 12 ¹/₂".
- Model FLTD II Twin Tub has an overall outside dimensions of 40" x 24" x 13 ⁷/₈", and inside dimensions (each compartment) of 19" x 18 ⁷/₈" x 12 ¹/₂".

OPTIONS

- Deck type faucet (4" center set) with 6 ³/₄" spout. (A-1)
- Overflow pipe with "O" ring to fit 1 ¹/₂" strainer. (A-2)
- Polypropylene faucet block, 5 ¹/₈" x 1 ¹/₂" x 1 ¹/₄" for installing clamp-on or integral clamp faucets to deck to accept overhead water supplies. (A-3)
- Faucet for top supplies. Clamps on with swing spout and angled nose end. (A-17)
- Deck type faucet (8" center set) with spout. (A-18)



