

SPECIFICATION

Seamless die-drawn construction of type 304, 18-8 stainless steel. Interior and top surfaces polished to a non-porous Hand-Blended Just Finish with highlighted bowl rim. Fully coated underside insulates for sound, and reduces condensation. Straight-sided compartment with 13/4" radius corners provides greater capacity. Self-rimming top mount Grip-Rim Plus with 300 series stainless steel mounting channels. Conforms to ASME/ANSI A112.19.3M. Drain punch #35 centered for Just J-35 unless otherwise specified.

To be specified:

- Faucet hole punching:
- ☐ (1) Hole Centered
- ☐ (2) Holes on 4" centers
- ☐ (3) Holes on 4 "centers(illustrated)
- ☐ (4) Holes on 4" centers
- ☐ Alternate Punching:


Faucet Model:


Punching required:

FUNCTIONAL DESIGN, QUALITY, AND SPECIFICATIONS LISTED DESCRIBE THE JUST STANDARD OF QUALITY. WHEN MAKING COMPARISONS TO OTHER OFFER-

NGS, INSIST ON THE JUST QUALITY OF CONSTRUCTION.				
Job Name				
Architect/Engineer				
APPROVED FOR MANUFACTURING				
MODEL NO	QTY			
COMPANY				
TITLE	DATE			
SIGNATURE				

DL - SERIES - B - 20 GA. SPACE SAVER - LEDGE TYPE





MODEL NO.	Α	В	O	D	Е	F	CUTOUT*
DL-1625-B-GR	16	25	10	10	41/2	2	15 ¹ / ₄ x 24 ¹ / ₄
DL-17537-B-GR	17 ¹ / ₂	37	111/2	16	41/2	2	16 ³ / ₄ x 36 ¹ / ₄
DL-1829-B-GR	18	29	12	12	41/2	2	17 ¹ / _{4 x 28 1/₄}
DL-1925-B-GR	19	25	14	10	3 ¹ / ₂	1 3/4	18 ¹ / ₄ x 24 ¹ / ₄
DL-1933-B-GR**	19	33	14	14	3 ¹ / ₂	13/4	18 ¹ / ₄ x 32 ¹ / ₄
DL-2025-B-GR	20	25	14	10	4 ¹ / ₂	2	19 ¹ / _{4 x 24} ¹ / ₄
DL-2037-B-GR	20	37	14	16	4 ¹ / ₂	2	19 ¹ / _{4 × 36} ¹ / ₄
DL-2128-B-GR	21	28	16	111/2	3 ¹ / ₂	13/4	20 ¹ / _{4 × 27} ¹ / ₄
DL-2228-B-GR	22	28	16	111/2	41/2		21 ¹ / ₄ x 27 ¹ / ₄

^{*} Cutout dimensions shown (Front-to-Back) x (Left-to-Right) - Corners of cutout may be square or up to 1/2" radius.

** This model has 1 1/8 center partition and 1 15/16 end flanges



ust manufacturing company 9233 KING STREET, FRANKLIN PARK, ILLINOIS 60131 PHONE: (847) 678-5150 FAX: (847) 678-6817