

MALLEABLE FITTINGS

WARD MANUFACTURING LLC

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET (MSDS) Page 1 of 5

DATE: April, 1997
UPDATED July, 2008

CONFORMS TO REQUIREMENTS OF OSHA STANDARD 1910.1200 "HAZARD COMMUNICATION"
AND TO VARIOUS STATE "EMPLOYEE RIGHT TO KNOW" LAW

SECTION I - PRODUCT IDENTIFICATION

This MSDS supplied for: **MALLEABLE IRON CASTINGS**

ASTM ALLOY DESIGNATION

A 47	Grade 32510	
A 197		
A 220	Grade 40010	Grade 50005
	Grade 45006	Grade 60004
	Grade 45008	Grade 70003

VENDOR NAME AND ADDRESS- WARD MANUFACTURING LLC
117 Gulick St. / P.O. Box 9
Blossburg, PA 16912

EMERGENCY PHONE NUMBER (570) 638 - 2131

FIRE HAZARD CLASS: HEALTH: 0 FLAMMABILITY: 0 REACTIVITY: 0
THE FOURTH DIAMOND:

ANSI: CAUTION: WELDING, CUTTING, OR GRINDING ON THIS CASTING
WILL GENERATE TOXIC DUST AND FUMES

N/E means none established

N/A means not applicable

N/D means no data available.

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET (MSDS) Page 2 of 5
 DATE: April, 1997
 UPDATED July, 2008

SECTION II - HAZARDOUS COMPONENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>PERCENT</u>	<u>TLV</u>	<u>PEL</u>
Carbon	7440-44-0	2.5-3.5	N/E	N/E
Silicon	7440-21-3	0.8-2.0	10 mg/cu.m	15 mg/cu-m
Manganese	7439-96-5	0.2-0.8	C5 mg/cu-m as dust 1 mg/cu.m as fume	C5 mg/ou- as dust
Nickel	7440-02-0	0.10	1 mg/cu.m	1 mg/cu.m
Chromium	7440-47-3	0.02-0.15	.5 mg/cu.m	1 mg/cu.m
Chromium (hexavalent)			.05 mg/cu.m	N/E
Aluminum	7429-90-5	0.003-0.20	10 mg/cu.m	N/E
Copper	7440-50-8	0.11-0.21	.2 mg/cu.m as fume 1 mg/cu.m as dust	.1mg/cu.m as fume 1 mg/cu.m as dust
Iron	7439-89-6	92.9-96.6	5 mg/cu-m as fume	10mg/cu.m as fume
Cerium	7440-45-1	0.01-0.40	N/E	N/E
Nitrogen	7727-37-9	0.002-0.15	N/E	N/E

Water insoluble hexavalent chromium is classified as a human carcinogen by the American Conference of Governmental Industrial Hygienists (ACGIH).

Approximately 66% of the total chromium (in welding fume) is hexavalent, and only 5% of that is insoluble. Considering the small amount of chromium in the casting, over-exposure to hexavalent chromium is not likely. (There is no hexavalent chromium in the alloy or its dust).

N/E means none established

N/A means not applicable

N/D means no data available.

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET (MSDS) Page 3 of 5
DATE: April, 1997
UPDATED July, 2008

SECTION III - OVERVIEW

There are no chemical hazards from these castings in solid form.

Dust or fumes generated by machining, grinding, or welding on the castings will put contaminants in the air. Since the casting is more than 90 percent iron, most of the dust or fumes will be iron or iron oxide. There is no TLV for iron dust, but available information indicates that a concentration of 10 mg/cu.m. as if it were a nuisance dust, will serve as a guideline until a TLV is established.

High production dry machining of malleable iron castings usually requires local exhaust ventilation.

Flame cutting, arc gouging, or welding on the casting generates iron oxide fume. Inhalation of too much iron oxide fume over a long time can cause siderosis, sometimes called "iron pigmentation" of the lung. It can be seen on a chest x-ray but causes little or no disability. Also see the Material Safety Data Sheet for the welding rod being used.

Welding or flame cutting may convert a fraction of the chromium to the water insoluble hexavalent (carcinogenic) form, but the chromium content of the castings is so low that over-exposure is not likely.

Nickel has been shown to cause cancer in laboratory animals. However, its potential to cause cancer in humans has not been determined. The nickel content of the casting is so low that over-exposure is not likely.

Other toxic metals in the alloy are present in small amounts that will not represent a hazard if copper dust and fume are adequately controlled.

Grinding on castings that have not been cleaned or that contain embedded silica will generate significant amounts of dust containing free silica, which can cause silicosis. Good local ventilation is frequently required to prevent over-exposure in this situation. If good ventilation is not available, use a NIOSH-approved dust respirator.

N/E means none established

N/A means not applicable

N/D means no data available.

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET (MSDS) Page 4 of 5
DATE: April, 1997
UPDATED July, 2008

SECTION IV - PHYSICAL DATA

Physical Description:	Solid, silver gray in color, no odor.
Boiling Point:	2750° C for iron
Vapor Pressure:	N/A
Vapor Density:	N/A
Solubility in Water:	N/A
Specific Gravity:	7.86 for iron
Percent Volatile By Volume:	N/A
Evaporation Rate:	N/A

SECTION V - FIRE AND EXPLOSION DATA

Castings will not burn or explode.

SECTION VI - HEALTH HAZARD DATA

<u>EYES:</u>	Metal particles in the eyes may cause irritation if not removed.
<u>SKIN:</u>	None known.
<u>BREATHING:</u>	Prolonged or repeated over-exposure to iron oxide produced in grinding or welding may cause siderosis.
<u>SWALLOWING:</u>	N/A
<u>NOISE:</u>	Grinding or machining Castings is noisy. The OSHA limit for noise averaged over 8 hours is 90 decibels (dBA), hearing conservation program required if exposure is over 85 dBA. If noise is at or above 90 dBA, you should wear ear muffs or ear plugs.

FIRST AID

<u>IF IN EYES:</u>	Metal particles should be removed by trained individuals such as a nurse or physician.
<u>IF ON SKIN:</u>	N/A
<u>IF BREATHED:</u>	(Fumes from welding): Move to fresh air.
<u>IF SWALLOWED:</u>	N/A

N/E means none established

N/A means not applicable

N/D means no data available.

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET, (MSDS) Page 5 of 5
DATE: April, 1997
UPDATED July, 2008

SECTION VII - REACTIVITY DATA

HAZARDOUS POLYMERIZATION: Will not occur.
STABILITY: Stable
INCOMPATIBILITY: Iron may cause violent decomposition of hydrogen peroxide (52% by weight or greater).

SECTION VIII - SPILL OR LEAK PROCEDURES

- STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED -

If damaged, return castings to vendor or send to scrap reclaimer.

Collected dust from machining, welding, etc. may be classed as a "hazardous waste" depending on circumstances. Consult local authorities regarding disposal.

SECTION IX - PROTECTIVE EQUIPMENT TO BE USED

RESPIRATORY PROTECTION: Wear a NIOSH approved respirator for dusts or fume if concentrations exceed the TLV or PEL.

VENTILATION: Provide general ventilation and/or local exhaust if necessary to maintain concentrations below the TLV's.

PROTECTIVE GLOVES: Work gloves advisable for handling castings.

EYE PROTECTION: Safety glasses with side shields and/or face shields for particles (grinding). Welding goggles or helmet for welding.

OTHER PROTECTIVE EQUIPMENT: Wear a protective apron and gauntlets if arc air gouging or cutting, or welding on castings. If noise is at or above 90 dBA you should wear ear muffs or ear plugs.

SECTION X - SPECIAL PRECAUTIONS OR OTHER COMMENTS

STORAGE: Keep dry to reduce rusting.

The information herein is based on the vendors MSDS with additions as necessary to comply with current regulations. The information is believed to be accurate, but under the circumstances is not warranted to be.

N/E means none established

N/A means not applicable

N/D means no data available.

WARD MANUFACTURING LLC
MATERIAL SAFETY DATA SHEET (MSDS) Page 1 of 5
DATE: April, 1997
UPDATED July, 2008

CONFORMS TO REQUIREMENTS OF OSHA STANDARD 1910.1200 "HAZARD COMMUNICATION"
AND TO VARIOUS STATE "EMPLOYEE RIGHT TO KNOW" LAW

SECTION I - PRODUCT IDENTIFICATION

This MSDS supplied for: **MALLEABLE IRON CASTINGS**

ASTM ALLOY DESIGNATION

A 47	Grade 32510	
A 197		
A 220	Grade 40010	Grade 50005
	Grade 45006	Grade 60004
	Grade 45008	Grade 70003

VENDOR NAME AND ADDRESS- WARD MANUFACTURING LLC
117 Gulick St. / P.O. Box 9
Blossburg, PA 16912

EMERGENCY PHONE NUMBER (570) 638 - 2131

FIRE HAZARD CLASS: HEALTH: 0 FLAMMABILITY: 0 REACTIVITY: 0
THE FOURTH DIAMOND:

ANSI: CAUTION: WELDING, CUTTING, OR GRINDING ON THIS CASTING
WILL GENERATE TOXIC DUST AND FUMES

N/E means none established

N/A means not applicable

N/D means no data available.

NSF Product and Service Listings

These Listings were Last Updated on **Monday, July 21, 2008** at 4:15 AM Eastern Time.
Please contact NSF International to confirm the status of any Listing, report errors, or make suggestions.

Warning: NSF is concerned about fraudulent downloading and manipulation of website text. If you have received this listing in hard copy, always confirm this certification/listing information by going directly to <http://www.nsf.com/Certified/PwsComponents/Listings.asp?Company=71950&Standard=061> for the latest most accurate information.

NSF/ANSI STANDARD 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. [Click here for a list of Abbreviations used in these Listings.](#)

WARD MANUFACTURING, INC.

115 GULICK STREET
P.O. BOX 9
BLOSSBURG, PA 16912-0009
570-638-2131

Facility : BLOSSBURG, PA

Pipes and Related Products

Trade Designation	Size	Water Contact Temp	Water Contact Material
Fittings			
Malleable Iron Fittings - Galvanized	1" - 4"	C. HOT	GALV
Cast Iron Fittings - Galvanized	1" - 4"	C. HOT	GALV



**VIZI.EX1904
Fittings, Malleable Iron**

Page Bottom

Fittings, Malleable Iron

See General Information for Fittings, Malleable Iron

WARD MFG INC
115 GULICK ST
PO BOX 9
BLOSSBURG, PA 16912 USA

EX1904

Extra heavy weight pattern in sizes 1/4 to 2 in. incl., for working pressures not exceeding 500 psi.

Configuration	Size In.	Rated Pressure (psig)
90 Degree Elbow	1/8, 1/4, 3/8, 1/2,	300
	3/4, 1, 1-1/4, 1-1/2,	
	2, 2-1/2, 3, 4	
45 Degree Elbow,	1/8, 1/4, 3/8, 1/2,	300
	3/4, 1, 1-1/4, 1-1/2,	
	2, 2-1/2, 3, 4	
90 Degree Street Elbow,	1/8, 1/4, 3/8, 1/2,	300
	3/4, 1, 1-1/4, 1-1/2,	
	1-1/2x1-1/4, 2, 2-1/2, 3	
45 Degree Street Elbow,	1/8, 3/8, 1/2, 3/4,	300
	1, 1-1/4, 1-1/2, 2	
Tee	1/8, 1/4, 3/8, 1/2,	300
	3/4, 1, 1-1/4, 1-1/2,	
	2, 2-1/2, 3, 4	
Street Tee	3/4, 1, 1-1/4	300
Crosses	1/2, 3/4, 1,	300
	1-1/4, 1-1/2, 2	
Coupling	1/8, 1/4, 3/8, 1/2, 3/4,	300
	1, 1-1/4, 1-1/2, 2, 2-1/2	
Reducing Coupling,	1/8, 1/4, 3/8, 1/2,	300
	3/4, 1, 1-1/4, 1-1/2,	
	2, 2-1/2, 3, 4	

Cap	1/4, 3/8, 1/2, 3/4,	300
	1, 1-1/4, 1-1/2, 2,	
	2-1/2, 3, 4	
Extension Piece	3/8, 1/2, 3/4, 1	300
90 Degree	1/4x1/8-3x2	300
Reducing Elbow		
Reducing Tees	1/2x1/4x1/2, 3/4x3/4x1/4,	300
	1/2x1/2x3/8, 3x2x2	
Return Bends	1/2, 3/4	300
Plugs	1/4, 3/8, 1/2, 3/4, 1	300
	1-1/4, 1-1/2, 2, 2-1/2,	
	3, 3-1/2, 4, 5, 6, 8	
Bushings	1/4x1/8-8x6	300

Last Updated on 1998-06-04

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2008 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

